



## Specification:

- \*Quick connect terminal block
- \*Adhesive and screws mount
- \*Breakaway flanges
- \*Easy installaion
- \*Colors: White, Brown, Grey
- \*Safety approvals:



| Part Number | Loop Type | Reed Form | Gap [Inch(mm)] | Maximum Initial Contact Resistance (ohm) | Maximum Contact Rating (W) | Maximum Switching Voltage (VDC/VAC) | Maximum Switching Current (A) |
|-------------|-----------|-----------|----------------|--|----------------------------|-------------------------------------|-------------------------------|
| MCS-3202    | Closed    | N/O       | 1 (25)         | 0.150                                    | 10                         | 100                                 | 0.5                           |
| MCS-3202A   | Open      | N/C       | 1 (25)         | 0.150                                    | 3                          | 30                                  | 0.2                           |

|   |             |                   |              |
|---|-------------|-------------------|--------------|
| <b>DSW</b> NINGBO DSW AUDIO & SECURITY EQUIPMENT<br><a href="http://www.dswbrand.com">http://www.dswbrand.com</a> , fax: +86(574)87264916 |             | Magnetic Contacts |              |
| MCS-3202  |             | E4.840.013        |              |
| No.   | DESCRIPTION | APPROVED          | DATE         |
| DATE OVERHAULED   | APPROVALS   | CHECKED           |              |
| X   | XX          |                   |              |
| 90° FORMED ±2°  |             |                   |              |
| FIRST ANGLE PROJECTION  |             | APPROVED          | 04.05.28     |
|   |             | SCALE             | NOT TO SCALE |
|   |             | SHEET             | VER 1.0      |