

Model No.: EML818


Holding Force: 180kg

• FEATURES:

- * Perfect for all kinds of doors, specially for exit-door and fire-resistant door.
- * Anodized aluminum Housing.
- * 12 VDC.
- * No residual magnetism.
- * Detachable mounting bracket.
- * MOV surge protection
- * Complete mounting hardware included.
- * 0.63-inch hookup wire included.




· DIMENSIONS:





Specifications	EML-818
Power	12VDC
Magnet Size	8⅓ox 5⅔ x %oin.
	(205 x 36 x 23.5 mm)
Armature Size	4 ⁹ /₁₀ x1 ³ /₁₀ x ³ /₁₀in.
	(125 x 35 x 9.5 mm)
Holding Force	396 ib. (180kg)
Current Drain	300mA @ 12VDC
Voltage Tolerance	± 10%
Housing	Aluminum
Temperature	14° ~ 131°F
	(-10° ~ 55°C)
Weight	1.1kg 2.42ib


· ELECTROMAGNETIC LOCK Installation Manual

▶ FIG.1












▶ FIG.2





Drill an 8mm hole thru door. From sexnut bolt sideof door, drill 12.7mm (1/2") hole, 25mm (1") in depth.



^{*} The information contained herein is believed to be correct, but no guarantee for accuracy, completeness DSW Electronics. Ltd. reseves the right to make changes without notification.

